BL15000C-1X-R-5463 SPECIFICATIONS

BEHLMAN's BL15000C-1X-R-5463 (15 KVA Frequency Converter) is a ruggedized, 19" rack mount system.

INPUT: 115/200 VAC, 3 Phase WYE/Delta, 324-596 Hz,

Utilizes a Multi Pulse Input Transformer for Low Input Current THD.

OUTPUT:

Power: 15,000 VA

Voltage: 115/200 VAC, 3 Phase

Frequency: 400 Hz Current: 37 Amps / Phase Current Crest Factor: 3:1

Power Factor: 100% of rated output into any

power factor load.

Distortion: 3% Typical THD

Load Regulation: $\pm 0.7\%$ No Load to Full Load Line Regulation: $\pm 0.1\%$ for $\pm 10\%$ Line Change

Efficiency: 80% typical.

PROTECTIVE CIRCUITS:

Input Protection: Electronic circuit breaker.

Constant Current Mode: Overload automatically causes voltage fold back to provide

maximum current without distorting output waveform. With LED Indicator.

Short Circuit Protection: Short Circuit electronically latches output open to protect load.

Power restored by recycling circuit breaker. With LED Indicator.

Thermal Protection: Internal temperature sensor prevents heat damage. With LED Indicator.

CONTROL/INDICATORS:

External Sync: Allows synchronization of the AC output with an external sine wave.

Line Drop Compensation: Allows for front panel adjustment of output to compensate for

voltage drop over long distance.

Meters: Three (3) DMM: True RMS Volts; True RMS Amps; Frequency

MECHANICAL SPECIFICATIONS:

Configuration: Two (2) 19" Rack Mount Chassis w/slides. Dimensions: Power/Input Chassis - 8.75"H x 22"D.

Control/Output Chassis - 7.00"H x 22"D.

Total Weight: Approximately 200 lbs.

Operating Temperature: 0 to + 55°C.

Humidity: 0-95% RH non-condensing.
Input connections: Barrier strips on rear.
Output: Barrier strip on rear

Grounding: Ground Stud on each chassis.

OPTION 5463: Special input transformer

Input - 115/200 VAC, 3 Phase WYE/Delta, 324-596 Hz

Output - Fixed at 115/200 VAC, 400Hz

Option R: Ruggedized

Slides - Option S10 (Behlman part no.101-085-010 & 101-085-006)

BEHLMAN

e-mail: sales@behlman.com Web-site: www.behlman.com